

New
2011 Model

ProJet™ DP 3000

Professional 3D Printer

Dental CAD/CAM 3D Printer Wax-Up Production

CREATE WITH CONFIDENCE.

This Dental Professional 3D Printer accurately, consistently and economically manufactures precision wax-ups for dental labs.

The system can generate hundreds of units each cycle with an extremely smooth surface finish that can be cast or pressed with conventional techniques.

ACCURACY • CAPACITY • COMPATIBILITY



Features

- Email notification capability *New*
- Uniformly thin wax-ups
- Push button operation
- Extra large build area *New*
- Accurate and consistent parts
- Wide range of indications for wax-ups

Benefits

- High efficiency and remote monitoring capability
- 20% average alloy savings and 50% less finishing
- Easy operation, no daily calibration needed
- Hundreds of units daily capacity
- Perfect fits, every time
- Fast ROI



For more information about 3D Systems' Professional 3D Printers, visit toptobottomdental.com or printin3d.com



ProJet™ DP 3000

Professional 3D Printer

Extend Innovation. Extend Production. Extend Choices.

Printing Modes
HD - High Definition
UHD - Ultra High Definition

New

Net Build Volume (xyz)
HD Mode: 298 x 185 x 203mm (11.75 x 7.3 x 8 inches)
UHD Mode: **203 x 178 x 152mm (8 x 7 x 6 inches)**

Resolution
HD Mode: 328 x 328 x 606 DPI (xyz)
UHD Mode: 656 x 656 x 800 DPI (xyz)

Accuracy (typical) 0.001-0.002 inch (0.025-0.05 mm) per inch of part dimension
accuracy may vary depending on build parameters, part geometry and size,
part orientation, and post-processing methods

New

Email Notice Capability **Yes**

Build Material
VisiJet® DP200 Build Material Formulated for exceptional castability

Support Material
VisiJet® S100 Support Material Non-toxic wax material for hands-free melt-away supports

Material Packaging
Build materials in clean 0.5 kg cartridges (machine holds up to 10 with auto-indexing)
Support materials in clean 0.405 kg cartridges (machine holds up to 10 with auto-indexing)

Electrical 100-127 VAC, 50/60 Hz, single-phase, 15A; 200-240* VAC, 50 Hz, single-phase, 10A

Dimensions (WxDxH)
3D Printer Crated 883 x 1420 x 1778mm (34.75 x 56 x 70 inches)
3D Printer Uncrated 737 x 1215 x 1504mm (29 x 47.8 x 59.2s inches)

Weight
3D Printer Crated 385 kg (850 lbs)
3D Printer Uncrated 254 kg (560 lbs)

ProJet™ Accelerator Software
Easy build job set-up, submission and job queue management
Automatic part placement and build optimization tools
Extensive part editing tools
Automatic support generation
Job statistics reporting tools

Network Compatibility Network ready with 10/100 Ethernet interface

Client Hardware Recommendation 1.8 GHz with 1GB RAM (OpenGL support 64 mb video RAM) or higher

Client Operating System Windows XP Professional, Windows Vista, Windows 7

Input Data File Formats Supported STL and SLC

Operating Temperature Range 18-28 °C (64-82 °F)

Noise < 65 dBA estimated (at medium fan setting)

Certifications CE

* Requires small external transformer supplied by 3D Systems in the provided country kit.

www.toptobottomdental.com

www.printin3d.com



333 Three D Systems Circle
Rock Hill, SC 29730 USA
Telephone +1(803) 326-3948
moreinfo@3dsystems.com

Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

© 2011 by 3D Systems, Inc. All rights reserved. Specifications subject to change without notice. ProJet™, RealWax™ are trademarks, and VisiJet® and the 3D logo are registered trademarks of 3D Systems, Inc.

PN 70732 Issue Date February 2011